

DC Load Isolation Switch

Main/ Maintenance Switch

125 x 100 x 120 mm

16A ~ 32A

IP65, full insulation.

In compliant with standards IEC/EN 60204 and IEC/EN 60947-3 (BS/EN 60947-3).

The main switch used as emergency-stop equipment with black handle and gray lock ring, can be locked in the 0 (Off) position according to IEC/EN 60204-1.



Type

Circuit Diagram Emblem	Basic Type	Poles /Contacts	Rated Continuous Current Ie (A)	Rated Continuous Voltage Ue (V)	Rated Continuous Power Pe (KW)
	DC-16A500V	2/4	16	500	8
	DC-20A450V	2/4	20	450	9
	DC-20A500V	2/4	20	500	10
	DC-32A250V	2/4	32	250	8
	DC-32A450V	2/4	32	450	14.5
	DC-25A450V	2/5	25	450	11.5
	DC-25A500V	2/5	25	500	12.5
	DC-20A650V	2/6	20	650	13
	DC-32A650V	2/6	32	650	21

Note



Load isolation switch can be used as maintenance switch or main switch with enclosure, connecting kinds of electric loads. Several padlocks can be assembled in the opening position, in order to ensure personnel safety, the opening position shall be clear and can't reset automatically. This safety switch conforms to standards BS/EN 60947-3.